

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF THE
UTAH-COLORADO STATE BOUNDARY LINE

BETWEEN MILE POSTS 11 AND 18

THE

NORTH BOUNDARY (EIGHTH STANDARD PARALLEL SOUTH)

THE

SOUTH BOUNDARY

AND

THE SUBDIVISIONAL LINES,

IN

TOWNSHIP 41 SOUTH, RANGE 26 EAST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

RONALD K. BAUGH
Cadastral Surveyor

Under special instructions dated and approved **May 2, 2005**, which
provided for the surveys included under Group Number **997**, and
assignment instructions dated **May 2, 2005**

Survey commenced **May 2, 2005**
Survey completed **July 21, 2005**

INDEX DIAGRAM

Township 41 South, Range 26 East

7	8	10	11	MP 18
6	39 5	29 4	22 3	7
38	38	28	21	MP 17
7	37 8	28 9	21 10	6
36	36	27	20	MP 16
18	35 17	26 16	19 15	5
34	34	26	19	MP 15
19	33 20	25 21	18 22	4
33	32	25	17	MP 14
30	31 29	24 28	17 27	3
31	30	23	16	MP 13
31	29 32	23 33	15 34	3
12	13	14	15	MP 12
				2
				MP 11

TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN

The following field notes are those of the dependent resurveys of the Utah-Colorado State boundary line between mile posts 11 and 18, the north boundary (Eighth Standard Parallel South) the south boundary, and the subdivisional lines, in T. 41 S., R. 26 E., Salt Lake Meridian, Utah.

History of Surveys

Surveyed by		Retr. or Resurveyed by	
EAST BOUNDARY (UTAH COLORADO STATE BOUNDARY)			
All	R.J. Reeves	1878	
All			A.W. Wilson 1885
Portion			C.R. Burt 1915
Portion			R.C. Yundt 1942-44
NORTH BOUNDARY (Eighth Standard Parallel South)			
Portion	A.D. Ferron	1884	
All			H.D. Page & J.M. Lentz 1899
SOUTH BOUNDARY			
All	H.D. Page & J.M. Lentz	1889	
WEST BOUNDARY			
All	H.D. Page & J.M. Lentz	1899	
All			J.F. Carroll 2004
SUBDIVISION			
All	H.D. Page & J.M. Lentz	1899	

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 997, dated May 2, 2005.

The true meridian direction and length of all lines were determined by the Global Positioning System (GPS), utilizing Real-Time Kinematic (RTK) observations using the Trimble 5700 model receiver.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

Geodetic control was derived using Global Positioning System (GPS) static survey observations, and post-processed by the National Geodetic Survey's (NGS) On-line Positioning Users Service (OPUS), utilizing Continually Operating Reference Stations: (CORS),

TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN

FREDONIA, CARBON COUNTY, and AZTEC. The N.A.D. 1983 (CORS96) geographic position of mile post No. 12 on the Utah-Colorado State Boundary line, is as follows:

Latitude: 37° 10' 22.124" N. Longitude: 109° 02' 44.396" W.
N.A.D. 1983, N.A.V.D. 1988 Elevation: 4939.5 ft.

Dependent Resurvey of the Utah-Colorado State Boundary Line
Between Mile Posts 11 to 18

Reestablishment of the Survey Executed by R.J. Reeves in 1878, the Resurvey by A.W. Wilson in 1885, the Resurvey by C.R. Burt in 1915 from the witness corner of Mile Post 11 to Mile Post 15, and the Resurvey by R.C. Yundt in 1942-44 from Mile Post 15 to Mile Post 18.

CHAINS

From the witness corner for Mile Post 11, monumented with an iron post, 3 inches diameter, firmly set and projecting 16 inches above ground, with a mound of stone, 4 ft. base, 2 ft. high, west of the corner, with brass cap marked as described in the official record of the 1915 resurvey.

Corner is located in a 4 strand barbed wire fence bearing north and south.

N. 0° 35.9' W., on the 12th Mile of the Utah-Colorado State Boundary Line.

0.200

The true point for Mile Post 11, at proportionate distance, falls in a deep wash, not monumented.

40.254

Point for the Mile Post 11 1/2, at proportionate distance, there is no remaining evidence of the original corner, not monumented.

73.158

Point for the closing corner of sections 3 and 34, Tps. 41 and 42 S., R. 26 E., at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a collar of stone, with brass cap marked:

T41S R26E
C S34 |
C S3 |
T42S
2005

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the stainless steel post.

**DEPENDENT RESURVEY OF THE UTAH-COLORADO STATE BOUNDARY,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

Corner is located 114 links west of the bottom of a wash, on a steep east slope, and in a 4 strand barb wire fence, bears north and south.

80.308

Mile Post 12, monumented with a iron post, 3 inches diameter, firmly set 18 in a mound of stone, 3 ft. base to top of brass cap marked as described in the official record of the 1915 resurvey.

Corner is located in a barb wire fence, bearing north and south.

N. 0° 40.2' W., on the 13th Mile of the Utah-Colorado State Boundary Line.

39.995

Point for the 1915 Mile Post No. 12 1/2, at proportionate distance, there is no remaining evidence of the original corner, not monumented.

72.986

Point for the closing corner of sections 27 and 34, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E
C S27 |
C S34 |
2005

Raise a mound of stone, 3 ft. base, 3 ft. high, west of the stainless steel post.

Corner is located on top of a sandy mesa and 10.6 links west of a 4 strand barb wire fence, bearing north and south.

79.990

Mile Post 13, monumented with an iron post, 2 1/2 inches diameter, firmly set in a mound of stone, with brass cap marked as described in the official record of the 1957 resurvey under Group No. 434, Colorado.

From this corner, a 3 inch diameter iron post, marked as described in the official record of the 1915 resurvey, was found wired to a north and south fence line, bearing east, 26.5 links distance. This corner was not utilized in the course of this survey.

N. 0° 08.3' E., on the 14th Mile of the Utah-Colorado State Boundary Line.

36.576

Point for Mile Post No. 13 1/2, at proportionate distance, there is no remaining evidence of the original corner, not monumented.

**DEPENDENT RESURVEY OF THE UTAH-COLORADO STATE BOUNDARY,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

- 73.052** Mile Post 14, monumented with a iron post, 3 inches diameter, firmly set, projecting 3 inches above ground, with brass cap marked as described in the official record of the 1915 resurvey.
- Corner is located in a fence line, bearing north and south.
-
- N. 2° 10.1' E., on the 15th mile of the Utah-Colorado State Boundary Line.
- 0.178** The closing corner of sections 22 and 27, monumented with a sandstone, 14x9x4 inches, dimly marked CC, lying loose, in a small mound of stone.
- At the corner point
- Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:
- | | |
|-----------|--|
| T41S R26E | |
| C S22 | |
| C S27 | |
| 2005 | |
- Deposit the marked sandstone alongside the stainless steel post.
- Raise a mound of stone, 3 ft. base, 2 ft. high, west of the corner.
- 43.811** Mile Post 14 1/2, monumented with an iron post, 2 1/2 inches diameter, firmly set in a small mound of stone, 3 ft. base to the top of brass cap marked as described in the official record of the 1957 resurvey under Group No. 434, Colorado.
- Corner is located 53.0 link north of the center of a dirt road bearing east and west.
-
- N. 1° 47.8' E., beginning new measurement.
- 30.167** Mile Post 15, of the 1878 R.J. Reeves survey, monumented with a sandstone, 16x10x4 inches, firmly set and plainly marked MPC on the east face, in a small mound of stone. This corner was accepted as an angle point in the 1957 resurvey under Group No. 434, Colorado.
- At the corner point (Angle Point)
- Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, with brass cap marked:

DEPENDENT RESURVEY OF THE UTAH-COLORADO STATE BOUNDARY,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN

CHAINS

AP
|
2005

Deposit the marked sandstone alongside the stainless steel post.

Corner is located on a small mesa, 150.0 links east of a north and south, 4 strand barb wire fence.

This corner will function as an angle point only.

N. 1° 03.6' W., beginning new measurement.

6.262 Point for the closing corner of sections 15 and 22, at proportionate distance, there is no remaining evidence of the original corner.

Set a brass tablet, 3 1/4 inch diameter, 3 1/2 inch stem, flush with the sandstone, in cement bound, into a drill hole on solid rock marked:

T41S R26E
C S15 |
C S22 |
2005

Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, west of the brass tablet.

13.600 Mile Post 15, monumented with a iron post, 3 inches diameter, firmly set and projecting 18 inches above ground, with brass cap marked:

15M
MON 157
| COL
UTAH |
| UIR
1914

Raise a mound of stone, 4 ft. base to the top of the brass cap.

Corner is located in a north and south fence line.

N. 0° 08.1' W., on the 16th mile of the Utah-Colorado State Boundary Line.

72.404 Point for the closing corner of sections 10 and 15, at proportionate distance, there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF THE UTAH-COLORADO STATE BOUNDARY,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 2 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 6 ft. base, to top of brass cap marked:

T41S R26E
C S10 |
C S15 |
2005

Corner is located on a north sloping spur, 50.0 links west of a wash, and 125.0 links west of a north and south fence line.

79.347

Mile Post 16, monumented with a iron post, 3 inches diameter, firmly set in a mound of stone, 4 ft. base to top of brass cap marked as described in the official record of the 1944 resurvey.

Corner is located on a north slope about 110.0 links west of a north and south fence line.

N. 0° 17.2' W., on the 17th mile of the Utah-Colorado State Boundary Line.

73.110

Point for the closing corner of sections 3 and 10, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, with a magnet at base and in a mound of stone, 5 ft. base to top of brass cap marked:

T41S R26E
C S3 |
C S10 |
2005

Corner is located on a south semi-steep west facing slope.

80.066

Mile Post 17, monumented with an iron post, 3 inches diameter, firmly set and projecting 18 inches above ground, with brass cap marked:

17M
UTAH | COLO
T41S
R26E
S3
1944

Raise a mound of stone, 4 ft. base, to top of brass cap.

**DEPENDENT RESURVEY OF THE UTAH-COLORADO STATE BOUNDARY,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

N. 0° 11.1' W., on the 18th mile of the Utah-Colorado State Boundary Line.

72.939

Intersect the closing corner of sections 3 and 34, Tps. 40 and 41 S., R. 26 E. (Eighth Standard Parallel South), monumented with a sandstone, 21x11x5 inches, in a mound of stone, dimly marked U on the west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with brass cap marked:

SC	
T40S R26E	
C S34	
C S3	
T41S	
2005	

Raise a mound of stone, 2 ft. base, 2 ft. high, west of stainless steel post.

Corner is located 150.0 links west of the edge of a rim.

79.803

Mile Post 18, monumented with a iron post, 3 inches diameter, loosely set and projecting 28 inches above ground, I built a mound of stone 4 ft. base, to top of brass cap marked

18 MP	
UT	
T40S	COL
R26E	
S34	
1944	

Dependent Resurvey of the North Boundary,
(Eighth Standard Parallel South)
T. 41 S., R. 26 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by A.D. Ferron
in 1884, and the Dependent Resurvey Executed by
H.D. Page and J.M. Lentz in 1899

From the standard corner of T. 40 S., Rgs. 25 and 26 E., on the Eighth Standard Parallel South, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set, in a collar of stone, with brass cap marked as described in the official record of the 2004 resurvey.

S. 88° 55.0' E., along the south boundary of section 31, T. 40 S., R. 26 E.

**DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

- 31.746** Point for the 1/4 section corner of section 6 only, on the north boundary of the township, falls in McElmo Creek, drains west south west, not monumented.
- 39.918** Point for the standard 1/4 section corner of section 31, T. 40 S., R. 26 E., at proportionate distance, falls in a cultivated field, there is no remaining evidence of the original corner, not monumented.
- 71.683** Point for the closing corner of section 5 and 6 on the north boundary of the township, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, with brass cap marked:

$$\begin{array}{c} \hline \text{S6} \mid \text{S5} \\ \text{C} \mid \text{C} \\ \hline \text{T41S R26E} \\ 2005 \end{array}$$

Set a 5 ft. steel fence post alongside the stainless steel post.

Corner is located in dense tamarisk.

- 79.836** Point for the standard corner of sections 31 and 32, T. 40 S., R. 26 E., at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, with brass cap marked:

$$\begin{array}{c} \text{SC} \\ \text{T40S R26E} \\ \hline \text{S31} \mid \text{S32} \\ \hline 2005 \end{array}$$

Set a 5 ft. steel fence post alongside the stainless steel post.

Corner is located in dense tamarisk.

S. 88° 55.0' E., along the south boundary of section 32, T. 40 S., R. 26 E.

- 31.745** Point for the 1/4 section corner of section 5 only, on the north boundary of the township.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, with a magnet at

**DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

base, in a mound of stone, 4 ft. base to top of brass cap marked:

1/4 S5
T41S R26E
2005

Corner is located on the east edge of a drainage, drains north.

39.918

The standard 1/4 section corner of section 32, T. 40 S., R. 26 E., monumented with a sandstone, 21x15x6 inches, plainly marked 1/4 on north face.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 6 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 5 ft. base to top of brass cap marked:

SC
T40S R26E
1/4 S32
2005

Deposit the marked sandstone alongside the stainless steel post.

Set a 5 ft. steel fence post alongside the stainless steel post.

N. 89° 57.0' E., beginning new measurement.

31.721

Point for the closing corner of sections 4 and 5 on the north boundary of the township, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with a magnet at base, with brass cap marked:

S5 | S4
C | C
T41S R26E
2005

Raise a mound of stone, 3 ft. base, 2 ft. high, south of the stainless steel post.

Corner is located on the point of a gray finger ridge which bears north and south, and at the south edge and base of a boulder, 4x3x3 ft. high.

**DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

39.963 Point for the standard corner of sections 32 and 33, T. 40 S., R. 26 E., at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with brass cap marked:

SC
T40S R26E
S32 | S33
2005

Corner is located on the west face of a very steep red and white clay slope, approx. 1/2 chain east of a 30 ft. ledge.

N. 89° 57.0' E., along the south boundary of section 33, T. 40 S., R. 26 E.

31.765 Point for the 1/4 section corner of section 4, on the north boundary of the township.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

1/4 S4
T41S R26E
2005

Corner is located in a grass flat on top of a large mesa.

39.963 The standard 1/4 section corner of section 33, monumented with a small mound of stone.

At the corner point (center of mound of stone).

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 4 ft. base to top of brass cap marked:

SC
T40S R26E
1/4 S33
2005

S. 89° 59.8' E., beginning new measurement.

31.809 Point for the closing corner of sections 3 and 4 on the north boundary of the township, at proportionate distance, there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

S4 | S3
CC
T41S R26E
2005

Raise a mound of stone, 3 ft. base, 2 ft. high, south of the stainless steel post.

Set a 5 ft. steel fence post alongside the stainless steel post.

Corner is located approx. 18 links west of a small drainage, drains south, on a south facing gradual slope.

40.062

Point for the standard 1/4 corner of sections 33 and 34, T. 40 S., R. 26 E., at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

SC
T40S R26E
S33 | S34
2005

Set a 5 ft. steel fence post alongside the stainless steel post.

Corner is located at the south edge of a cleared front lot, 2 1/2 chains southeast from the east side of a home.

S. 89° 59.8' E., along the south boundary of section 34, T. 40 S., R. 26 E.

31.824

Point for the 1/4 section corner of section 3 on the north boundary of the township.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a magnet at base in a mound of stone, 4 ft. base to top of brass cap marked:

1/4 S3
T41S R26E
2005

Corner is located on a steep clay finger ridge that bears south and north east.

**DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

40.077 True point for the standard 1/4 section corner of section 34, T. 40 S., R. 26 E., at proportionate distance, falls on inaccessible ground, not monumented.

43.868 The standard witness 1/4 section corner of section 34, monumented with a cross chiseled in solid sandstone and also marked WC 1/4 on north side.

At the corner point

Set a brass tablet, 3 1/4 inch diameter, with a 3 1/2 inch stem, flush with the sandstone, in cement bond, into a drill hole through the cross on solid rock marked:

WC
T40S R26E
← 1/4 S34
2005

S. 89° 39.4' E., beginning new measurement.

17.232 The closing corner of sections 3 and 34, Tps. 40 and 41 S., R. 26 E., on the Utah - Colorado State Boundary Line, hereinbefore described.

Dependent Resurvey of the South Boundary,
T. 41 S., R. 26 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
H.D. Page & J.M. Lentz in 1899

From the corner of sections 1, 6, 31 and 36, Tps. 41 and 42 S., Rs. 25 and 26 E., monumented with a stainless steel post, 2 1/2 inches diameter, firmly set in a collar of stone, with brass cap marked as described in the official record of the 2004 resurvey.

From this corner, Utah State Highway No. 262 south right-of-way marker bears N. 19° 46.5' E., 26.954 chains distance, monumented with a concrete post, 6 inches diameter with an unmarked 3 inch brass cap on top.

S. 89° 58.7' E., between sections 6 and 31.

39.936 Point for the 1/4 section corner of sections 6 and 31, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with brass cap marked:

13
DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN

CHAINS

T41S R26E
S31
1/4 —
S6
T42S
2005

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the stainless steel post.

Set a 5 ft. steel fence post alongside the stainless steel post.

79.872 Point for the corner of sections 5, 6, 31 and 32, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 3 1/2 ft. base to top of brass cap marked:

T41S R26E
S31 | S32
S6 | S5
T42S
2005

Corner is located near a pipeline and a fiber optical line, both bear northwesterly and southeasterly.

S. 89° 58.7' E., between sections 5 and 32.

27.550 Intersect the center line of Utah State Highway No. 262, not monumented.

39.936 Point for the 1/4 section corner of sections 5 and 32, at proportionate distance, there is no remaining evidence of the original corner position.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E
S32
1/4 —
S5
T42S
2005

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the stainless steel post.

**DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

Set a 5 ft. steel fence post alongside the stainless steel post.

Corner is located on open flat land.

- 79.872** The corner of sections 4, 5, 32 and 33, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set in a mound of stone with brass cap marked as described in the official record of the 2004 resurvey of T. 41 S., R. 25 E.

From this corner, Utah State Highway No. 162, north right-of-way Marker bears S. 30° 40.8' E., 37.555 chains distance, monumented with a concrete post, 6 inches diameter projecting 14 inches above the ground, with an unmarked 3 inch brass cap on top.

N. 89° 59.0' E., between section 4 and 33 on the south boundary of the township.

- 40.027** Point for the 1/4 section corner of sections 4 and 33, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E
S33
1/4 —
S4
T42S
2005

Set a 5 ft. steel fence post alongside the stainless steel post.

Corner is located on the east edge of a wash, 50 ft. wide, 3 ft. deep, drains south.

- 80.054** The corner of sections 3, 4, 33 and 34, monumented with a sandstone, 18x10x5 inches, firmly set and dimly marked with 3 notches on west edge, with a small mound of stone to the west.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground to bedrock, with a magnet at base, in a collar of stone, with brass cap marked:

T41S R26E
S33 | S34
S4 | S3
T42S
2005

**DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

Deposit marked stone alongside the stainless steel post.

Rebuild the mound of stone, 3 ft. base, 2 ft. high, west of the stainless steel post.

Corner is located on a north sloped about 15 links south of a draw, draining west.

N. 89° 55.7' E., between section 3 and 34.

40.063

The 1/4 section corner of sections 3 and 34, monumented with a mound of stone.

At the corner point (center of the mound of stone).

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E
S34
1/4 —
S3
T42S
2005

Raise a mound of stone, 2 ft. base, 1 ft. high, north of the stainless steel post.

S. 89° 32.9' E., Beginning new measurement.

29.420

The closing corner of section 3 and 34, T. 41 and 42 S., R. 26 E., on the Utah-Colorado State Boundary line, hereinbefore described.

Dependent Resurvey of the Subdivisional Lines,
T. 41 S., R. 26 E., Salt Lake Meridian, Utah

From the corner of sections 3, 4, 33 and 34, on the south boundary of the township, hereinbefore described.

N. 0° 05.7' E., between section 33 and 34.

40.108

The 1/4 section corner of sections 33 and 34, monumented with a broken sandstone, 19x13x4 inches, dimly marked 1/4.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground to bedrock, in a collar of stone, with a magnet at base, with brass cap marked:

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

T41S R26E
1/4
S33 | S34
2005

Deposit the marked stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the stainless steel post.

N. 0° 09.4' W., beginning new measurement.

39.989

Point for the corner of sections 27, 28, 33 and 34, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E
S28 | S27
S33 | S34
2005

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the stainless steel post.

Set a 5 ft. steel fence post alongside the stainless steel post.

Corner is located in open land between two small hills to the east and west.

S. 89° 51.4' E., between sections 27 and 34.

39.964

The 1/4 section corner of sections 27 and 34, monumented with a sandstone, 16x13x7 inches, plainly marked 1/4.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 4 ft. base to top of brass cap marked:

T41S R26E
S27
1/4 —
S34
2005

Deposit the marked stone alongside the stainless steel post.

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

S. 89° 54.6' E., beginning new measurement.

28.622

The closing corner of sections 27 and 34 on the Utah-Colorado State Boundary line, hereinbefore described.

From the corner of section 27, 28, 33 and 34.

N. 0° 11.6' E., between sections 27 and 28.

39.989

The 1/4 section corner of sections 27 and 28, monumented with a broken sandstone, 16x10x3 inches, plainly marked 1/4 on north face.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with brass cap marked:

T41S R26E		
1/4		
S28		S27
2005		

Deposit the marked stone alongside the stainless steel post.

Raise a mound of stone, 2 ft. base, 1 ft. high, west of the stainless steel post.

N. 0° 33.4' W., beginning new measurement.

39.754

The corner of sections 21, 22, 27 and 28, monumented with a sandstone, 36x7x5 inches, firmly set and plainly marked with 2 notches on the south and 3 notches on the east edges.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E		
S21		S22
S28		S27
2005		

Deposit the marked stone alongside the stainless steel post.

Corner is located on flat land about 4 links north of a small wash, drains east-south-east.

N. 89° 28.3' E., between section 22 and 27.

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

40.166 The 1/4 section corner of sections 22 and 27, monumented with a sandstone, 17x8x5 inches, plainly marked 1/4 on north face.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E
S22
1/4 —
S27
2005

Deposit the marked stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the stainless steel post.

S. 89° 56.6' E., beginning new measurement.

28.408 The closing corner of sections 22 and 27 on the Utah-Colorado State Boundary line, hereinbefore described.

From the corner of sections 21, 22, 27 and 28.

N. 0° 36.6' E., between sections 21 and 22.

40.410 The 1/4 section corner of sections 21 and 22, monumented with a sandstone, 14x6x5 inches, dimly marked 1/4 in a small mound of stone.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 4 ft. base to top of brass cap marked:

T41S R26E
1/4
S21 | S22
2005

Deposit the marked stone alongside the stainless steel post.

Corner is located in a small spur, 100 links south of a low rim that curves from southeast to southwest.

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

N. 0° 11.3' W., beginning new measurement.

39.919

The corner of sections 15, 16, 21 and 22, monumented with a cross cut into solid sandstone, below a mound of stone, 2 ft. base 1 ft. high.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, on top of the cross in solid sandstone, with a magnet at base, in a mound of stone, 5 ft. base to top of brass cap marked:

T41S R26E	
S16	S15
S21	S22
2005	

N. 89° 58.5' E., between sections 15 and 22.

41.460

Point for the 1/4 section corner of sections 15 and 22, at proportionate distance, there is no remaining evidence of the original corner.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in cement bond, into a drill hole on solid rock marked:

T41S R26E	
S15	
1/4	—
S22	
2005	

Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, north of brass tablet.

Corner is located on a rim at the head of a draw, drains north.

70.742

The closing corner of sections 15 and 22 on the Utah-Colorado State Boundary line, hereinbefore described.

From the corner of section 15, 16, 21 and 22.

N. 0° 11.0' E., between sections 15 and 16.

39.877

The 1/4 section corner of sections 15 and 16, monumented with a sandstone, 18x8x6 inches, dimly marked 1/4, in a small mound of stone.

At the corner point

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 4 ft. base to top of brass cap marked:

T41S R26E
1/4
S16 | S15
2005

Deposit the marked stone alongside the stainless steel post.

N. 0° 22.0' E., beginning new measurement.

39.928

Point for the corner of sections 9, 10, 15 and 16, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 4 inches in the ground to bedrock, in a mound of stone, 5 ft. base to top of brass cap marked:

T41S R26E
S9 | S10
S16 | S15
2005

Corner is located on a semi-steep north east facing slope in a large boulder area.

S. 89° 57.6' E., between sections 10 and 15.

40.000

The 1/4 section corner of sections 10 and 15, monumented with a sandstone, 12x10x7 inches, with no marks visible, in a small mound of stone and with old lath around it.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 5 ft. base to top of brass cap marked:

T41S R26E
S10
1/4 —
S15
2005

Deposit the unmarked stone alongside the stainless steel post.

Corner is located on the east slope of a mesa, near the head of a draw, drains northeast.

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

S. 89° 59.5' E., beginning new measurement.

30.037

The closing corner of sections 10 and 15 on the Utah-Colorado State Boundary line, hereinbefore described.

From the corner of section 9, 10, 15 and 16.

N. 0° 14.2' W., between sections 9 and 10.

39.928

The 1/4 section corner of sections 9 and 10, monumented with a cross on east end of a boulder that is 10x6x4 ft.

At the corner point (cross on boulder)

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in cement bond, into a drill hole on solid rock marked:

T41S R26E	
1/4	
S9	S10
2005	

Raise a mound of stone, 3 ft. base, 2 ft. high, west of brass tablet on the boulder.

N. 0° 02.3' W., beginning new measurement.

40.028

The corner of sections 3, 4, 9 and 10, monumented with a sandstone, 26x14x7 inches, plainly marked with 3 notches on the east and 5 notches on the south edges.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E	
S4	S3
S9	S10
2005	

Deposit the marked stone alongside the stainless steel post.

Raise a mound of stone, 4 ft. base, 3 ft. high, west of the stainless steel post.

Corner is located on a west facing slope.

N. 89° 56.9' E., between sections 3 and 10.

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

- 40.452** Point for the 1/4 section corner of sections 3 and 10, at proportionate distance, there is no remaining evidence of the original corner.
- Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 3 ft. base to top of brass cap marked:
- T41S R26E
S3
1/4 —
S10
2005
- Corner is located on a gradual east facing slope in large boulders.
- 69.780** The closing corner of sections 3 and 10 on the Utah-Colorado State Boundary line, hereinbefore described.
-
- From the corner of section 3, 4, 9 and 10.
- N. 0° 06.2' E., between sections 3 and 4.
- 38.029** Point for the original witness 1/4 section corner of sections 3 and 4, at proportionate distance, there is no remaining evidence of the original witness corner.
- 39.353** Point selected for the witness 1/4 section corner of sections 3 and 4.
- Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in cement bond, into a drill hole on solid rock marked:
- WC
T41S R26E
S4 ↑ S3
2005
- Raise a mound of stone, 3 ft. base, 2 ft high, north of the brass tablet.
- The witness corner is located on the east rim of ledges, 60 ft. high.
- 40.030** True point for the 1/4 section corner of sections 3 and 4, at proportionate distance, falls on inaccessible ledges.
- 80.060** The closing corner of sections 3 and 4 on the north boundary of the township (Eight Standard Parallel South), hereinbefore described.
-

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

From the corner of sections 4, 5, 32 and 33, on the south boundary of the township, hereinbefore described.

N. $0^{\circ} 02.8'$ E., between sections 32 and 33.

40.030

Point for the $1/4$ section corner of sections 32 and 33, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 $1/2$ inches diameter, 24 inches in the ground, with brass cap marked:

T41S R26E
1/4
S32 | S33
2005

Set a 5 ft. steel fence post alongside the stainless steel post.

Corner is located on a gentle northeast slope in deep sand.

80.060

The corner of sections 28, 29, 32 and 33, monumented with a sandstone, 17x12x4 inches, in a mound of stone, dimly marked, with 4 notches on the east and 1 notch on the south edges.

At the corner point

Set a stainless steel post, 30 inches long, 2 $1/2$ inches diameter, 16 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 3 ft. base to top of brass cap marked:

T41S R26E
S29 | S28
S32 | S33
2005

Deposit the marked stone alongside the stainless steel post.

From the corner of sections 27, 28, 33 and 34.

S. $89^{\circ} 57.4'$ W., between sections 28 and 33.

39.965

Point for the $1/4$ section corner of sections 28 and 33, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 $1/2$ inches diameter, 4 inches in the ground to bedrock, in a mound of stone, 6 ft. base to top of brass cap marked:

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

T41S R26E
S28
1/4 —
S33
2005

Corner is located on the south slope of a spur that projects east.

79.930 The corner of sections 28, 29, 32 and 33.

N. 0° 04.7' E., between sections 28 and 29.

40.028 The 1/4 section corner of sections 28 and 29, monumented with a cross on solid sandstone.

At the corner point

Set a brass tablet, 3 1/4 inches diameter, 3 1/2 inch stem, flush with the sandstone, in cement bond, into a drill hole on solid rock marked:

T41S R26E
1/4
S29 | S28
2005

Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, west of the brass tablet.

N. 0° 04.4' W., beginning new measurement.

40.023 The corner of sections 20, 21, 28 and 29, monumented with a sandstone, 16x12x3 inches, in a small mound of stone, dimly marked with 2 notches on south edge only.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E
S20 | S21
S29 | S28
2005

Deposit the marked stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the stainless steel post.

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

From the corner of sections 21, 22, 27 and 28.

N. 89° 49.3' W., between sections 21 and 28.

39.830

Point for the 1/4 section corner of sections 21 and 28, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with brass cap marked:

T41S R26E
S21
1/4 —
S28
2005

Set a 5 ft. steel fence post alongside the stainless steel post.

Corner is located in gently rolling open land.

79.660

The corner of sections 20, 21, 28 and 29.

N. 0° 17.2' W., between sections 20 and 21.

39.654

The 1/4 section corner of sections 20 and 21, monumented with a sandstone, 12x10x3 inches, dimly marked 1/4, with a 5/8 inch rebar, 18 inches long, next to sandstone, with a red cap marked UT RLS and last 3 numbers visible are 004.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E
1/4
S20 | S21
2005

Deposit the marked stone and 5/8 inch rebar with cap alongside the stainless steel post.

N. 0° 27.9' E., beginning new measurement.

40.397

The corner of sections 16, 17, 20 and 21, monumented with a sandstone, 12x10x4 inches, marked with 4 notches on the east and 3 notches on the south edges.

At the corner point

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E	
S17	S16
S20	S21
2005	

Deposit the marked stone alongside the stainless steel post.

Raise a mound of stone, 2 ft. base, 1 ft. high, west of the stainless steel post.

From the corner of sections 15, 16, 21 and 22.

N. 89° 47.5' W., between sections 16 and 21.

39.751

The 1/4 section corner of sections 16 and 21, monumented with a sandstone, 15x10x7 inches, in a small mound of stone, dimly marked 1/4.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 3 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 5 ft. base to top of brass cap marked:

T41S R26E	
S16	
1/4	—
S21	
2005	

Deposit the marked stone alongside the stainless steel post.

Corner is located on a gentle northeast slope of a mesa in widely scattered juniper trees.

S. 89° 45.1' W., beginning new measurement.

40.062

The corner of sections 16, 17, 20 and 21.

N. 0° 08.3' E., between sections 16 and 17.

39.930

Point for the 1/4 section corner of sections 16 and 17, at proportionate distance, there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E
1/4
S17 | S16
2005

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the stainless steel post.

Set a 5 ft. steel fence post alongside the stainless steel post.

Corner is located on a gentle rolling mesa.

79.860

The corner of sections 8, 9, 16 and 17, monumented with a sandstone, 14x9x9 inches, marked with 4 notches on the east and south edges.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 4 ft. base to top of brass cap marked:

T41S R26E
S8 | S9
S17 | S16
2005

Deposit the marked stone alongside the stainless steel post.

From the corner of sections 9, 10, 15 and 16.

WEST, between section 9 and 16.

40.000

The 1/4 section corner of sections 9 and 16, monumented with a sandstone, 16x9x4 inches, dimly marked 1/4.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E
S9
1/4 —
S16
2005

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

Deposit the marked stone alongside the stainless steel post.

N. 89° 57.6' W., beginning new measurement.

39.987 The corner of sections 8, 9, 16 and 17.

N. 0° 00.5' E., between sections 8 and 9.

39.978 Point for the 1/4 section corner of sections 8 and 9, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E
1/4
S8 | S9
2005

Raise a mound of stone, 2 ft. base, 2 ft. high, south of the stainless steel post.

Corner is located on a steep west facing slope.

79.956 The corner of sections 4, 5, 8 and 9, monumented with a cross on solid sandstone, with a small mound of stone to the west.

At the corner point (cross on solid sandstone)

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in cement bond, into a drill hole on solid rock marked:

T41S R26E
S5 | S4
S8 | S9
2005

Rebuild the mound of stone, 4 ft. base, 2 ft. high, west of brass tablet.

From the corner of sections 3, 4, 9 and 10.

N.89° 53.6' W., between sections 4 and 9.

39.859 The 1/4 section corner of sections 4 and 9, monumented with a sandstone, 18x16x6 inches, dimly marked 1/4, with a small mound of stone to the north.

At the corner point

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 3 ft. base to top of brass cap marked:

T41S R26E
S4
1/4 —
S9
2005

Deposit the marked stone alongside the stainless steel post.

S. 89° 55.9' W., beginning new measurement.

39.964 The corner of sections 4, 5, 8 and 9.

N. 0° 02.7' W., between sections 4 and 5.

34.995 Point for the original witness 1/4 section corner of sections 4 and 5, at proportionate distance, there is no remaining evidence of the original corner, not remonumented.

39.994 Point for the 1/4 section corner of sections 4 and 5, at proportionate distance.

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in cement bond, into a drill hole on top of a small solid sandstone boulder marked:

T41S R26E
1/4
S5 | S4
2005

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the brass tablet.

79.988 The closing corner of sections 4 and 5 on the north boundary of the township (Eight Standard Parallel South), hereinbefore described.

From the corner of section 5, 6, 31 and 32, on the south boundary of the township, hereinbefore described.

N. 0° 11.8' W., between sections 31 and 32.

4.306 Intersect the center line of Utah State Highway No. 162, not monumented.

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS**40.015**

The 1/4 section corner of sections 31 and 32, monumented with a sandstone, 18x18x8 inches, in a small mound of stone and marked 1/4 on west face.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E
1/4
S31 | S32
2005

Deposit the marked stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the stainless steel post.

N. 0° 05.6' E., beginning new measurement.

40.013

The corner of sections 29, 30, 31 and 32, monumented with a sandstone, 16x12x4 inches, dimly marked, in a small mound of stone, with 5 notches on the east and 1 notch on the south edges.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E
S30 | S29
S31 | S32
2005

Deposit the marked stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of stainless steel post.

From the corner of sections 28, 29, 32 and 33.

N. 89° 59.9' W., between sections 29 and 32.

39.987

The 1/4 section corner of sections 29 and 32, monumented with a sandstone, 12x8x7 inches, plainly marked 1/4.

At the corner point

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, firmly set, with a magnet at base, with brass cap marked:

T41S R26E
S29
1/4 —
S32
2005

Deposit the marked stone alongside the stainless steel post.

S. 89° 59.8' W., beginning new measurement.

39.997 The corner of sections 29, 30, 31 and 32.

N. 89° 56.5' W., between sections 30 and 31.

39.904 The 1/4 section corner of sections 30 and 31, monumented with a sandstone, 16x9x7 inches, plainly marked 1/4.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E
S30
1/4 —
S31
2005

Deposit the marked stone alongside the stainless steel post.

Raise a mound of stone, 4 ft. base, 3 ft. high, north of the stainless steel post.

N. 89° 43.4' W., beginning new measurement.

39.790 The corner of sections 25, 30, 31 and 36, on the west boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set in mound of stone, with brass cap marked as described in the official record of the 2004 resurvey.

From the corner of sections 29, 30, 31 and 32.

N. 0° 09.5' E., between sections 29 and 30.

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS**39.952**

The 1/4 section corner of sections 29 and 30, monumented with a sandstone, 16x14x3 inches, dimly marked 1/4.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 4 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 5 ft. base to top of brass cap marked:

T41S R26E
1/4
S30 | S29
2005

Deposit the marked stone alongside the stainless steel post.

N. 1° 05.8' W., beginning new measurement.

40.007

Point for the corner of sections 19, 20, 29 and 30, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with brass cap marked:

T41S R26E
S19 | S20
S30 | S29
2005

Set a 5 ft. steel fence post alongside the stainless steel post.

Corner is located 1.50 chains north of an improved road.

From the corner of sections 20, 21, 28 and 29.

S. 89° 55.8' W., between sections 20 and 29.

40.320

Point for the 1/4 section corner of sections 20 and 29, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with brass cap marked:

T41S R26E
S20
1/4 —
S29
2005

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the stainless steel post.

Set a 5 ft. steel fence post alongside the stainless steel post.

Corner is located 10.0 links east of a wash, 4 ft. wide, 1 ft. deep, drains south.

80.640 The corner of sections 19, 20, 29 and 30.

N. 89° 15.2' W., between sections 19 and 30.

40.323 The 1/4 section corner of sections 19 and 30 monumented with a sandstone, 12x10x4 inches, plainly marked 1/4.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E
S19
1/4 —
S30
2005

Deposit the marked stone alongside the stainless steel post.

S. 89° 10.9' W., beginning new measurement.

39.380 The corner of sections 19, 24, 25 and 30, on the west boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, projecting 3 inches above ground, with brass cap, marked as described in the official record of the 2004 resurvey.

From the corner of sections 19, 20, 29 and 30.

N. 0° 32.4' E., between sections 19 and 20.

40.001 Point for the 1/4 section corner of sections 19 and 20, at proportionate distance, there is no remaining evidence of the original corner. This point is located on a large inaccessible boulder at the head of a draw, drains north.

From this true point, the point selected for the offline witness 1/4 section corner, bears S. 0° 59.2' W., 2.347 chains distance.

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

Set a brass tablet, 3 1/4 inches diameter, with 3 1/2 inch stem, flush with sandstone, in cement bond, into a drill hole on solid rock marked:

T41S R26E
WC
S19 ↑ S20
2005

Raise a mound of stone, 3 ft. base, 2 ft. high, west of brass tablet.

Corner is located on top of a ledge and rim of a mesa, 50 ft. high, curves from northwest to northeast.

80.002

Point for the corner of sections 17, 18, 19 and 20, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 6 inches in the ground to bedrock, in a mound of stone, 8 ft. base to top of brass cap marked:

T41S R26E
S18 | S17
S19 | S20
2005

Corner is located on a steep rocky east slope in scattered juniper.

From the corner of sections 16, 17, 20 and 21.

S. 89° 53.6' W., between sections 17 and 20.

40.000

Point for the 1/4 section corner of sections 17 and 20, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, with brass cap marked:

T41S R26E
S17
1/4 —
S20
2005

Set a 5 ft. steel fence post alongside the stainless steel post.

Corner is located on rolling mesa land, 25 links east of a wash, 4 ft. wide, 2 ft. deep, drains north.

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

80.000 The corner of sections 17, 18, 19 and 20.

S. 89° 56.1' W., between sections 18 and 19.

39.980 Point for the 1/4 section corner of sections 18 and 19, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with brass cap marked:

T41S R26E
S18
1/4 —
S19
2005

Set a 5 ft. steel fence post alongside the stainless steel post.

Corner is located in open mesa land.

79.960 The corner of sections 13, 18, 19 and 24, on the west boundary of the township, monumented with a brass tablet, 3 1/4 inches diameter, set flush on a sandstone boulder, with brass tablet marked as described in the official record of the 2004 resurvey.

From the corner of sections 17, 18, 19 and 20.

N. 0° 14.7' E., between sections 17 and 18.

40.000 Point for the 1/4 section corner of sections 17 and 18, at proportionate distance, there is no remaining evidence of the original corner.

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 8 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 5 ft. base to top of brass cap marked:

T41S R26E
1/4
S18 | S17
2005

Corner is located on a south facing slope in an area of black boulders.

80.000 Point for the corner of sections 7, 8, 17 and 18, at proportionate distance, there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 4 ft. base to top of brass cap marked:

T41S R26E	
S7	S8
S18	S17
2005	

Corner is located on a gentle northwest facing black rock slope.

From the corner of sections 8, 9, 16 and 17.

N. 89° 38.7' W., between sections 8 and 17.

39.743

The 1/4 section corner of sections 8 and 17, monumented with a sandstone, 22x9x3 inches, plainly marked 1/4.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with brass cap marked:

T41S R26E	
S8	
1/4	—
S17	
2005	

Deposit the marked stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the stainless steel post.

Corner is located in a small draw, drains north.

S. 89° 37.9' W., beginning new measurement.

40.094

The corner of sections 7, 8, 17 and 18.

S. 89° 51.5' W., between sections 7 and 18.

40.094

The 1/4 section corner of sections 7 and 18, monumented with a small scattered mound of stone.

At the center of the mound of stone

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, with a magnet at base, in a collar of stone, with brass cap marked:

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

T41S R26E
S7
1/4 —
S18
2005

Set a 5 ft. steel fence post alongside the stainless steel post.

Corner is located on gravel flat on a north facing slope.

S. 89° 40.5' W., beginning new measurement.

42.480

The corner of sections 7, 12, 13 and 18, on the west boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, projecting 5 inches above ground in a collar of stone, with brass cap marked as described in the official record of the 2004 resurvey.

From the corner of sections 7, 8, 17 and 18.

N. 0° 00.4' W., between sections 7 and 8.

40.000

The 1/4 section corner of sections 7 and 8, monumented with a sandstone, 20x12x4 inches, plainly marked 1/4, in a small mound of stone.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 4 ft. base to top of brass cap marked:

T41S R26E
1/4
S7 | S8
2005

Deposit the marked stone alongside the stainless steel post.

N. 0° 00.9' E., beginning new measurement.

40.001

The corner of sections 5, 6, 7 and 8, monumented with a sandstone, 17x10x8 inches, plainly marked with 5 notches on the east and south edges.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground to bedrock, with a magnet at

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

base, in a mound of stone, 5 ft. base to top of brass cap marked:

T41S R26E	
S6	S5
S7	S8
2005	

Deposit the marked stone alongside the stainless steel post.

Corner is located on top of a spur, bears northwest.

From the corner of sections 4, 5, 8 and 9.

N. 89° 57.3' W., between sections 5 and 8.

39.936

The 1/4 section corner of sections 5 and 8, monumented with a sandstone, 16x12x4 inches, firmly set and marked 1/4 on the north face.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with brass cap marked:

T41S R26E	
	S5
1/4	—
	S8
2005	

Deposit the marked stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the stainless steel post.

WEST, beginning new measurement.

39.891

The corner of sections 5, 6, 7 and 8.

S. 89° 59.0' W., between sections 6 and 7.

40.094

The 1/4 section corner of sections 6 and 7, monumented with a sandstone, 15x9x8 inches, firmly set in the ground, with a small mound of stone, to the north.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with brass cap marked:

**DEPENDENT RESURVEY OF THE SUDIVISIONAL LINES,
TOWNSHIP 41 SOUTH, RANGE 26 EAST, SALT LAKE MERIDIAN**

CHAINS

T41S R26E
S6
1/4 —
S7
2005

Deposit the marked stone alongside the stainless steel post.

Rebuild mound of stone, 4 ft. base, 2 ft. high, north of the stainless steel post.

N. 89° 59.6' W., beginning new measurement.

- 40.131** The corner of sections 1, 6, 7 and 12, on the west boundary of the township, monumented with a stainless steel post, 2 1/2 inches diameter, firmly set in a mound of stone, 3 ft. base to top of brass cap, marked as described in the official record of the 2004 resurvey.

From the corner of sections 5, 6, 7 and 8.

N. 0° 01.4' W., between sections 5 and 6.

- 40.418** Point for the 1/4 section corner of sections 5 and 6, at proportionate distance, there is no remaining evidence of the original corner.
- Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, with a magnet at base, in a collar of stone, with brass cap marked:

T41S R26E
1/4
S6 | S5
2005

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the stainless steel post.

Corner is located on a north slope, 25 links south of a wash, drains northwest.

- 80.836** The closing corner of sections 5 and 6 on the north boundary of the township, (Eighty Standard Parallel South), hereinbefore described.
-

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Glen B. Hatch Tyler Trujillo	Cadastral Surveyor Survey Technician

CERTIFICATE OF SURVEY

I, **Ronald K. Baugh, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the **2nd day of May, 2005**, I have **executed a dependent resurvey of the Utah-Colorado state boundary line between mile posts 11 and 18, the north boundary (Eighth Standard Parallel South), the south boundary, and the subdivisional lines in Township 41 South, Range 26 East,**

of the **Salt Lake Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 26, 2006
Date

Ronald K. Baugh
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the **dependent resurvey of the Utah-Colorado state boundary line between mile posts 11 and 18, the north boundary (Eighth Standard Parallel South), the south boundary, and the subdivisional lines in Township 41 South, Range 26 East, Salt Lake Meridian, Utah,**

executed by **Ronald K. Baugh, Cadastral Surveyor,**

having been critically examined and found correct, are hereby approved.

April 28, 2006
Date

Daniel W. Webb
Chief Cadastral Surveyor for Utah